



The LED/COR/DIM is supplied either as a changeover module, which can be integrally mounted within the luminaire, or housed in a strain relief enclosure for remote mounting.

- Static Inverter Changeover Module
- Suitable for 50V AC/DC & 110V AC/DC Systems
- Holds EM Power from the Primary of the Driver
- Inhibits the Dimming State of the Load
- Available in Remote Enclosure if Required

Emergency lighting change over relays with an additional dimming inhibition relay that will restore a fitting that was running in a mains dimmed state, to full brightness for emergency operation.

Compatible with fluorescent and LED loads and runs in conjunction with either 50V AC/DC or 110V AC/DC central battery systems.

The associated control gear must be suitable for running from the emergency voltage.

## Order Codes

LED/COR/DIM-M	Supplied as a changeover module for integral mounting within a luminaire
LED/COR/DIM/R	The above module housed in a suitable Remote Enclosure with Strain Relief

## Technical Details:

Emergency Voltage	50 or 110 Volt AC/DC Nominal
Tc Temperature and Point	70°C Side Centre Can
Ambient Temperature	0°C - 50°C
Mains Supply	230-240V AC 50/60Hz
Power Rating	14.5mA $\lambda = 0.61$
Dimensions L x W x H	165mm x 45mm x 29mm (f/c 155mm)
Remote Enclosure Dimensions (if required)	340mm x 42mm x 89mm
Module Weight	0.32Kg