



The NDA/3 range is supplied as a conversion kit for integral use within a luminaire. If required, it can be provided within a suitable remote enclosure where space inside the fitting is limited.

- DALI Self-Test Conversion Module
- Deep discharge protection
- Low Power Consumption
- High Temperature NiCd Batteries
- Converts LED Loads from 6-80 Volts
- Can be Provided in Various Remote Enclosures

A 3 hour DALI self-test emergency lighting conversion kit which operates with high temperature NiCd batteries. The unit is designed to suit an extremely wide range of LED types and circuits. The NDA/3 automatically adjusts the output LED current to provide the best match between the battery and the load, providing maximum illumination whilst ensuring full battery duration.

Please see separate datasheets for Remote Enclosure details.

There are 2 main versions available -

Order Codes

NDA/3-K	For LED loads operating in voltage range of 6 - 55 Volts. For integral use.	NDA/3/80-K	For LED loads, operating in voltage range of 15 - 80 Volts. For integral use.
NDA/3/TP60	As above, housed in two part enclosure	NDA/3/80/TP60	As above, housed in two part enclosure
NDA/3/SP98	As above, housed in single enclosure	NDA/3/80/SP98	As above, housed in single enclosure

Technical Details:

Mains Supply	230-240V AC 50/60 Hz	Max Ta and Tc	Ta - 50 °C - Tc - 70 °C
Power Rating	26mA $\lambda = 0.88$	Max Battery temperature	55 °C
Duration	3 Hours	Battery Discharge Current	1000mA nominal
Recharge Period	24-Hours	Discharge Voltage Limit	2.5 Volts
Battery Size & Type	3.6V 4.5Ah NiCd Cells	Ingress Protection	IP20
Charge Current	200mA	Terminal - Screw & Push	1.0mm ² - 1.5 mm ²
Battery Current Limit	1000mA	Module Dimensions (LxWxH)	165x 45 x 29 (f/c 155mm)
Kit Weight	0.69Kg (M-0.29 B-0.40)	Battery Stick Dimensions (LxØ)	220 x 38 (f/c 205mm)