



The ELV/24A Range is supplied as a remote conversion kit for mounting away from the fitting. It is suitable for All 24V Loads.

- Low Voltage Conversion Kit
- Deep discharge protection
- Complete Kit Housed in One Enclosure
- High Capacity VRLA Batteries
- Converts 24V Loads Up To 100W
- 100% BLF In Emergency

A 3 hour remote conversion kit for 24V loads. This pack will power the load at 100% (BLF\*) for three hours in emergency. This kit is housed in a single hinged steel enclosure. The two packs will power Up To their rated Wattages and although they are Non-Maintained, they can be used in conjunction with the existing mains transformer to form a Maintained circuit.

\* BLF = Ballast Lumen Factor/the percentage output in emergency

There are 2 versions available -

## Order Codes

ELV/24A/40/NM3	Non-Maintained unit in single housing to power up to 40W of load
ELV/24A/100/NM3	Non-Maintained unit in single housing to power up to 100W of load

## Technical Details:

	ELV/24A/40/NM3	ELV/24A/100/NM3
Input Voltage	230-240V AC 50/60Hz	
Power Rating	46mA $\lambda = 0.53$	
Dimensions	385mm x 395mm x 105mm	
Battery Type	2 x 12V 7Ah	2 x 12V 17Ah
Overall Weight	11Kg	17Kg
Ingress Protection	IP20	
Ballast Lumen Factor	100%	