



- Surface Mount (Ceiling)
- White Polycarbonate body
- Translucent Polycarbonate Cover
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP65
- DDP (Deep Discharge Protection)
- Cree LED's
- Perfect for Warehouse Applications

A stylish and compact circular IP65 3 Watt or 6 Watt LED Bulkhead suitable for ceiling mounting applications. The 3W unit is available in either Switchable Maintained, Non-Maintained or as DALI Self-Test (3W only). The 6W unit is offered as non-maintained only. Either 390 lumens (3W) or 600 lumens (6W) this is an excellent solution for tall ceiling heights in damp locations. The unit utilises LiFePO4 battery technology which provides a far longer life than traditional battery types, making this an ideal product for difficult to maintain areas.

Order Codes

CB3S/3W/M3	CB3S/6W/NM3	CB3S/3W/DA
3W Non-Maintained	6W Non-Maintained	3W DALI Self-Test NM3
3W Maintained		

Technical Details:

Mains Supply	230-240V AC 50/60 Hz	230-240V AC 50/60 Hz	230-240V AC 50/60 Hz
Power Rating Maintained	55mA $\lambda = 0.6$		
Power Rating Non-Maintained	25mA $\lambda = 0.6$	25mA $\lambda = 0.6$	16mA $\lambda = 0.48$
Duration	3 Hours	3 Hours	3 Hours
Recharge Period	12 Hours – Electronic	12 Hours – Electronic	12 Hours – Electronic
Battery Size & Type	6.4V 3.0Ah LiFePO4 Cells	6.4V 6.0Ah LiFePO4 Cells	9.6V 1.5Ah LiFePO4 Cells
Charge Current	0-400mA Float	0-400mA Float	0-150mA Float
Ingress Protection Rating	IP65	IP65	IP65
Light Output	3 Watts	6 Watts	3 Watts
Light Source	1 x 3 Watt Cree LED	1 x 6W Cree LED	1 x 3W Cree LED
Lumen Output	390 Lumen *	600 Lumen *	390 Lumen *

* LDT Files Available