



- Surface Mount (Ceiling)
- White Polycarbonate body
- Translucent Polycarbonate Cover
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP41
- DDP (Deep Discharge Protection)
- Cree LED's
- High Output - 390 Delivered Lumen

A stylish and compact square Surface 3 Watt LED Bulkhead suitable for ceiling mounting. The unit is available as either Switchable Maintained, Non-Maintained, DALI Self-Test Switchable Maintained and DALI Self-Test Non-Maintained. Whilst the dimensions of this unit are kept very small, the output is an impressive 390 delivered lumen.

The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

### Order Codes

### Spacing Table at 0.5 Lux:

Order Code	Configuration	Ceiling Height	To Wall	Between Fittings
CB4S/3W/M3	Switchable Maintained	2.5m	3.5m	8.5m
CB4S/3W/NM3	Non-Maintained	3.0m	4.0m	9.5m
CB4S/3W/M3/DALI	DALI ST Maintained	3.5m	4.0m	10.5m
CB4S/3W/NM3/DALI	DALI ST Non-Maintained	4.0m	5.0m	11.0m
		4.5m	5.5m	12.5m
		5.0m	5.5m	13.5m

### Technical Details:

	CB4S	CB4S/DALI
Mains Supply	230-240V AC 50/60 Hz	
Power Rating	55mA $\lambda = 0.6$ Maintained	55mA $\lambda = 0.6$ Maintained
	25mA $\lambda = 0.6$ Non-Maintained	25mA $\lambda = 0.6$ Non-Maintained
Duration	3 Hours	
Recharge Period	12 Hours – Energy saving electronic charger	
Battery Size & Type	6.4V 3.0Ah LiFePO4 Cells	9.6V 1.5Ah LiFePO4 Cells
Charge Current	0-400mA Float	0-150mA Float
Ingress Protection Rating	IP41	
Light Output	3 Watts	
Light Source	1 x 3 Watt Cree LED	
Lumen Output	390 Delivered Lumen (LDT file available)	