



- Surface Mount (Ceiling)
- White Polycarbonate body
- Translucent Polycarbonate Cover
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP41
- DDP (Deep Discharge Protection)
- Cree LED's

A stylish and compact square Surface 3 Watt LED Bulkhead suitable for ceiling mounting. The unit is available in either a Switchable Maintained, Non-Maintained or as a DALI Self-Test version. Whilst the dimensions of this unit are kept very small, the output is an impressive 390 lumens.

The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

Order Codes

CB4S/3W/M3	Switchable Maintained
CB4S/3W/NM3	Non-Maintained
CB4S/3W/DA	DALI Self-Test

Spacing Table at 0.5 Lux:

Ceiling Height	To Wall	Between Fittings
2.5m	3.5m	8.5m
3.0m	4.0m	9.5m
3.5m	4.0m	10.5m
4.0m	5.0m	11.0m
4.5m	5.5m	12.5m
5.0m	5.5m	13.5m

Technical Details:

Mains Supply	230-240V AC 50/60 Hz
Power Rating	55mA $\lambda = 0.6$ Maintained
	25mA $\lambda = 0.6$ Non-Maintained
Duration	3 Hours
Recharge Period	12 Hours – Energy saving electronic charger
Battery Size & Type	M3 Version = 6.4V 3.0Ah LiFePO4 Cells - DALI Version = 9.6V 1.5Ah LiFePO4 Cells
Charge Current	0-400mA Float
Ingress Protection Rating	IP41
Light Output	3 Watts
Light Source	1 x 3 Watt Cree LED
Lumen Output	390 Lumens (LDT Files available)