



- Surface Mount (Wall or Ceiling)
- Optional Recessed (Wall or Ceiling)
- Optional Pendant (Ceiling)
- White Polycarbonate body
- Translucent Polycarbonate Cover
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP65
- DDP (Deep Discharge Protection)
- Samsung LED's

A stylish and compact IP65 rated 3 Watt LED luminaire suitable for mounting a number of different ways. The unit is available in either a Switchable Maintained, Non-Maintained or DALI Self-Test version. The fitting is not only more compact than the majority of LED bulkheads, but offers an impressive 350 lumens.

The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

Order Codes

CB5S/3W/M3	Switchable Maintained IP65 High Output Bulkhead
CB5S/3W/NM3	Non-Maintained IP65 High Output Bulkhead
CB5S/3W/DA	DALI Self-Test IP65 High Output Bulkhead

Technical Details:

Mains Supply	230-240V AC 50/60 Hz		
Power Rating	55mA	$\lambda = 0.6$ Maintained	DALI = 40mA $\lambda = 0.6$ Maintained
	25mA	$\lambda = 0.6$ Non-Maintained	DALI = 16mA $\lambda = 0.48$ Maintained
Duration	3 Hours		
Recharge Period	12 Hours – Energy saving electronic charger		
Battery Size & Type	M3 = 6.4V 3.0Ah LiFePO4 Cells	DALI = 9.6V 1.5Ah LiFePO4 Cells	
Charge Current	Dual Rate Charge 0-400mA		
Ingress Protection Rating	IP65		
Light Output	3 Watts		
Light Source	8 pcs Samsung LED		
Lumen Output	350 Lumens (LDT Files available)		