



- Recessed mounting
- White Polycarbonate body
- Translucent Polycarbonate Cover
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP41
- 25m viewing distance
- ISO legends as standard
- DDP (Deep Discharge Protection)
- Samsung LED's

A stylish and compact Double Sided LED Exit Sign suitable for ceiling recess mount applications. The unit is available in either a Switchable Maintained/Non-Maintained or DALI Self-Test version. The unit is supplied with a Plexi glass screen printed legend plate which offers an impressive 25m viewing distance. The legend panels are available in either Arrow Up (AU), Arrow Down (AD) or Arrow Left/Right (ALAR). The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

Order Codes

CE1R/2W/M3/**	Switchable Maintained	** Please specify legend
CE1R/3W/DA/**	DALI Self-Test	required AU, AD, or ALAR

Technical Details:

	CE1R/2W/M3	CE1R/3W/DA
Mains Supply	230-240V AC 50/60 Hz	
Power Rating - Maintained	44mA $\lambda = 0.6$	40mA $\lambda = 0.6$
Duration	3 Hours	
Recharge Period	12 Hours – Energy saving electronic charger	
Battery Size & Type	6.4V 2.0Ah LiFePO4 Cells	9.6V 1.5Ah LiFePO4 Cells
Charge Current	0-400mA Dual Rate	0-150mA Dual Rate
Ingress Protection Rating	IP41	
Class	Class II	