



- Suspension Mounting
- White Polycarbonate Body
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP40 rated
- 30m Viewing Distance
- ISO Legends as Standard
- DDP (Deep Discharge Protection)
- Samsung LED's

A stylish and compact suspended Single Sided LED Exit Sign that can be surface mounted.

The unit is available in either a Switchable Maintained/Non-Maintained or a DALI Self-Test version. The unit comes with a Plexi glass screen printed legend plate which offers an impressive 30m viewing distance.

The legend panels are available in either Arrow Up (AU), Arrow Down (AD), Arrow Left (AL) or Arrow Right (AR).

The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

Order Codes

CE2S/SM/2W/M3/**	Switchable Maintained	** Please specify legend
CE2S/SM/3W/DA/**	DALI Self-Test	required AU, AD, AL or AR

Technical Details:

CE2S/SM/2W/M3

CE2S/SM/3W/DA

Mains Supply	230-240V AC 50/60 Hz	
Power Rating	55mA $\lambda = 0.6$	40mA $\lambda = 0.6$
Duration	3 Hours	
Recharge Period	12 Hours – Energy saving electronic charger	
Battery Size & Type	6.4V 3.0Ah LiFePO4 Cells	9.6V 1.5Ah LiFePO4 Cells
Charge Current	0-400mA Float	0-400mA Float
Ingress Protection Rating	IP40	
Class	Class II	