



- Suitable for Damp Locations i.e. Bathrooms
- Elliptical Lens for Corridor Applications
- Maximises Spacings
- Standard, Self-Test and DALI Options Available
- High Output - Up to 197 Delivered Lumen
- Supplied With Plugs and Leads
- Requires 43mm Cut-Out
- Features Bi-Colour Charge LED
- Independently Tested by The LIA

The LED/40/CO/IP54 is a discrete emergency LED which is designed for ceiling recess applications along corridors. The bezel has a diameter of 50mm and the cut out required is 43mm.

The main LED can be driven up to 700mA and provides up to 197 lumens. The body also features a bi-colour LED; green for charge healthy and red for fault indication of self-test functionality.

Order Codes

LED/40/CO/W	White (RAL9016) Emergency Device
LED/40/CO/S	Silver (RAL9006) Emergency Device
LED/40/CO/B	Black (RAL9005) Emergency Device

Spacing Table Along Corridor @ 700mA:

Mounting Height	To Wall		Between Fittings	
	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux
2.5m	5.2m	4.6m	11.9m	10.2m
3.0m	5.8m	5.1m	13.1m	11.4m
4.0m	6.9m	5.8m	15.6m	13.7m
5.0m	7.9m	5.0m	18.0m	15.5m
6.0m	8.3m	4.2m	20.1m	15.5m
8.0m	6.5m	-	21.9m	12.7m

Technical Details:

Input Voltage	4V DC Max	Output at 350mA	114 Delivered Lumen
Power Rating	3W	Output at 500mA	151 Delivered Lumen
Maximum Forward Current	700mA	Output at 700mA	197 Delivered Lumen
Light Source	Edison EDEW Series	Wiring Method	Series Connection via C4201 Plug
Beam Angle	125° x 50°	Ingress Protection	IP54 (front face only)
Light Source Colour Temperature	6000K	Dimensions	Ø 50mm x 45mm (min void 40mm)
Tc Max	80 ° LED Back Plate	Weight	0.065Kg