



The CT6S/6W/NM3 is a simple solution to your emergency lighting applications. The only connection required is a permanent Live, Neutral and Earth.

- Ingress Protection Rating - IP65
- Directional LED Heads
- Deep Discharge Protection
- High Capacity NiCd Batteries
- Available as Standard or DALI Self-Test
- Non-Maintained Operation
- Simple Installation
- 610 Lumen Output
- Photometrically Tested by The LIA

Suitable for damp or warehouse applications. The fitting features a factory fitted waterproof gasket to a high ingress protection rating.

The CT6S/6W/NM3 is available as either standard emergency of as DALI self-test. As per the DALI standard, if the DALI version is not connected to a control system, then the fitting will revert to standalone self-test operation. A more budget version is available, if required. Each head has an output of 3W, providing a total output of 6W.

There are 2 versions available -

Order Codes

CT6S/6/NM3	Non-Maintained with standard 3 hour emergency operation
CT6S/6/NM3/DA	Non-Maintained with 3 hour DALI self-test operation

Technical Details:

	CT6S/6/NM3	CT6S/6/NM3/DA
Input Voltage	230-240V AC 50/60Hz	
Power Rating	25mA $\lambda = 0.85$	26mA $\lambda = 0.88$
Dimensions	280mm x 300mm x 95mm	
Battery Type	7.2V 4.5Ah NiCd	
Overall Weight	2Kg	2.05Kg
Ingress Protection	IP65	
Electrical Classification	Class 1	
Ambient Temperature (Ta)	0 to 35°C	