



- 110 ° Open Area or Corridor Optic Options
- Standard, Self-Test and DALI Options Available
- High Output - Up to 207 Delivered Lumen
- 185mm Diameter x 42mm Depth
- White or Black 30% Gloss Finish
- Contains Kitemarked (HJT) Control Gear
- Maintained or Non-Maintained Operation

The MPR/M3 is a surface mount standalone emergency LED luminaire which can incorporate our open area or corridor 3W LEDs. The unit can be used as maintained or non-maintained. The main LED is driven at 700mA and provides either 207 delivered lumen with the open area lens or 197 delivered lumen with the corridor lens.

Order Codes

MPR//W/M3** White (RAL9016) Emergency Device

MPR//B/M3** Black (RAL9005) Emergency Device

** = OA for Open Area Lens and CO for Corridor Lens

Spacing Table with Open Area Lens:

Mounting Height	To Wall		Between Fittings	
	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux
2.5m	3.9m	3.6m	8.2m	7.6m
3.0m	4.5m	4.1m	9.4m	8.7m
4.0m	5.5m	4.8m	11.8m	10.9m
5.0m	6.4m	5.0m	14.0m	12.6m
6.0m	6.9m	3.1m	16.0m	13.3m
8.0m	6.0m	-	18.9m	8.5m

Technical Details:

Input Voltage	230-240V AC 50/60Hz	Lumen Output (OA)	207 Delivered Lumen
Power Rating	51mA - $\lambda = 0.51$	Lumen Output (CO)	197 Delivered Lumen
Charge Current	200mA Nominal	Battery Type	3.6V 4.5Ah NiCd
Duration	3 Hours	Mains Input Termination	0.75mm to 2.5mm Cable
Recharge Period	24 Hours	Ingress Protection	IP20
Light Source Colour Temperature	6000K	Dimensions	Ø 185mm x 42mm
Weight	1.1Kg	Ta Max	25 °
Beam Angle (OA)	110 °	Beam Angle (CO)	125 ° x 50 °