



Fixing Centres 150mm x M4

The S-DSP/4 DALI Self-Test range is supplied with a choice of LED emitters and is designed for ceiling recess applications. The maintained/non-maintained emergency driver is supplied with strain relief cables and passes through a 43mm aperture.

- Suitable for Ceiling Recess Applications.
- Deep Discharge Protection
- Plugs and Leads for Simple Installation
- High Capacity NiCd Batteries
- Strain Relief Module
- Can be Supplied without LED Where Required
- Suitable for 43mm or Greater Apertures
- Fully DALI Compliant

A 3 hour DALI Self-Test Emergency Lighting driver that operates at 700mA in both emergency and in switchable mains operation. This unit primarily is designed as your DALI emergency lighting driver, but can also be used for night lighting purposes via a timer switch, where required.

The module, batteries and LED all feature plugs and leads for simple installation.

There are 4 main versions available -

Order Codes

** - W = White (RAL9016) - B = Black (RAL9005) - S = Silver (RAL9006)

S-DSP/4/LED/40/OA/**	Complete 207 Lumen Emergency Solution with Open Area Lens LED
S-DSP/4/LED/40/CO/**	Complete 197 Lumen Emergency Solution with Corridor Lens LED
S-DSP/4/LED/40/NL/**	Complete 194 Lumen Emergency Solution with No Lens LED
S-DSP/4/LED/41/W	Complete 231 Lumen Emergency Solution with High Output LED and White Bezel

Technical Details:

Mains Supply	230-240V AC 50/60 Hz	Max Ta and Tc	Ta - 50 °C - Tc - 70 °C
Power Rating	18mA $\lambda = 0.49$	Max Battery Temperature	55 °C
Duration	3 Hours	Battery Discharge Current	1000mA nominal
Recharge Period	24-Hours	Discharge Voltage Cut Off	4.0 Volts
Battery Size & Type	4.8V 3.0Ah NiCd Cells	Ingress Protection	IP20
Charge Current	200mA	Mains Plug Input Cable (push)	1.0mm ² - 1.5 mm ²
Battery Current Limit	1000mA	Module Dimensions (LxWxH)	164mm x 35mm x 28mm
Overall Weight (with LED)	0.41Kg	Battery Dimensions (LxØ)	285mm x 27mm