



Fixing Centres 175mm

The MML Range is supplied as a split remote conversion kit for mounting away from the fitting. It is suitable for 230V DC Loads.

- Conversion Kit for Mains Voltage Lamps
- Deep discharge protection
- Split Pack Arrangement for Ceiling Voids
- Extra Long Life LiFePO4 Batteries
- Converts Loads Up To 8W
- Passes Through 60mm Aperture

A split pack, 3 hour remote conversion kit for 230V DC loads. This pack will power the load at 100% (EOFi*) for three hours in emergency.

The MML/8W/TP60 will power up to 8W of DC load.

* EOfi= Emergency Output Factor/the percentage output in emergency

Order Codes

| | |
|-------------|--|
| MML/8W/TP60 | Maintained Pack for 230V DC Loads up to 8W |
| CRL5 | White, ceiling recess charge LED holder |

NB: Please ensure that your lamp/luminaire is capable of being powered by DC voltage

Technical Details:

| | |
|--------------------------|-----------------------------|
| Input Voltage | 230-240 Volts AC 50/60 Hz |
| Input Current (Charging) | 5.3W 29mA $\lambda = 0.75$ |
| Input Current (Standby) | 1.5W 14mA $\lambda = 0.45$ |
| Battery Type | 12.8V 3.8Ah LiFePO4 |
| Enclosure Dimensions | 184mm L x 53mm W x 24.5mm H |
| Battery Dimensions | 159mm x 59mm x 42mm |
| Overall Weight | 0.67Kg |
| Ingress Protection | IP20 |