



- Surface Mount (Wall or Ceiling)
- Optional Recessed (Wall or Ceiling)
- Optional Pendant (Ceiling)
- White Polycarbonate body
- Translucent Polycarbonate Cover
- Extra Long Life LiFePO₄ cells
- Ingress Protection Rating - IP65
- Basic, DALI-2 or Wireless Operation
- Samsung LED's

A stylish and compact IP65 rated luminaire suitable for mounting a number of different ways. The unit is available as either Maintained, Non-Maintained, DALI-2 Self-Test, or Wireless self-test operation. The fitting is not only more compact than the majority of LED bulkheads, but offers an impressive 325 delivered lumen.

The batteries used with this unit not only offer double the life of traditional emergency lighting batteries, but consume far less power during their operation.

Order Codes

CB5S/M	Maintained/Non-Maintained IP65 High Output Bulkhead
CB5S/DA	Maintained/Non-Maintained DALI Self-Test IP65 High Output Bulkhead
CB5S/LMEM	Maintained/Non-Maintained Wireless Self-Test IP65 High Output Bulkhead

Technical Details:

	CB5S/M	CB5S/DA
Mains Supply	230-240V AC 50/60 Hz	
Power Rating (Charging - Maintained) *	5.7W 31mA $\lambda = 0.75$	5W 28mA $\lambda = 0.74$
Power Rating (Charged) *	0.2W 8mA $\lambda = 0.1$	0.3W 8mA $\lambda = 0.15$
Duration	3-Hours	
Recharge Period	24-Hours	
Battery Size & Type	3.2V 3.8Ah LiFePO ₄ Cells	
Charge Current	225mA Nominal	
Ingress Protection Rating	IP65	
Light Source	8 pcs Samsung LED	
Lumen Output	325 Delivered Lumens	
Weight	0.75Kg	

* Following its initial charge, the unit will spend 90% of its operational life in standby mode