



- Ingress Protection Rating - IP65
- Directional LED Heads
- Deep Discharge Protection
- Extra Long Life LiFePO4 Batteries
- Ready for Connection to Casambi
- Non-Maintained Operation
- Simple Installation
- 610 Lumen Output
- Photometrically Tested by The LIA

There is 1 version available -

Order Codes

CT6S/6/NM/CASAMBI Casambi Ready Non-Maintained with standard 3 hour emergency operation

Technical Details:

Input Voltage	230-240V AC 50/60Hz
Power Rating (Charged) *	1.4W 12mA $\lambda = 0.48$
Power Rating (Charging) *	4W 21mA $\lambda = 0.79$
Dimensions	280mm x 300mm x 95mm
Battery Type	6.4V 3.8Ah LiFePO4
Overall Weight	2.15Kg
Ingress Protection	IP65
Electrical Classification	Class 1
Ambient Temperature (Ta)	0 to 35°C

* Following its initial charge, the unit will spend 90% of its operational life in standby mode

The CT6S/6W/NM3/CASAMBI is a simple solution to your emergency lighting applications. The only connection required is a permanent Live, Neutral and Earth.

Suitable for damp or warehouse applications. The fitting features a factory fitted waterproof gasket to a high ingress protection rating.

The CT6S/6W/NM3/CASAMBI is supplied ready for connection to a Casambi wireless control system.

Each head has an output of 3W, providing a total output of 6W.

This product operates with the latest LiFePO4 batteries that offer a long life and a low parasitic load.