

Battery Types & Configuration - LiFePO4 TE (3 WIRE)

ALL BATTERIES WITH 3 WIRE TE CONNECTOR RED POSITIVE + YELLOW NTC TEMP TO 3 WIRE MODULE VIA PLUG IN CONNECTOR
 BLACK NEGATIVE - TO 2 WIRE MODULE VIA FLYING LEADS

1 Cell - 3.2V 3.8Ah LiFePO4 Plate - 1S1P
Type 2 - 1/LP38/S/TE

90mm(l) x Ø 28mm
 Fixing Centres 80mm x M4

1 Cell - 3.2V 3.8Ah LiFePO4 Tubed - 1S1P
Type T - 1/LP38/PT/TE

90mm(l) x Ø 35mm

LiFePO4	3.2V 3.8Ah	3.2V 4.8Ah	6.4V 3.8Ah	6.4V 4.8Ah	12.8V 3.8Ah
NLP/1	X				
NLP/1S		X			
NLP/2			X		
NLP/2S				X	
TLP/1	X				
TLP/1S		X			
TLP/S2			X		
TLP/2S				X	
D2N/1	X				
D2N/1S		X			
D2N/2			X		
D2N/2S				X	
T2N/1	X				
T2N/1S		X			
T2N/2			X		
T2N/2S				X	
ACD/1	X				
ADM/1	X				
BMM/1	X				
S/ALP1	X				
MML/4W/TP60			X		
MML/8W/TP60					X

2 Cell - 6.4V 3.8Ah LiFePO4 Plate - 2S1P
Type 2 - 2/LP38/S/TE

157mm(l) x Ø 28mm
 Fixing Centres 147mm x M4

2 Cell - 6.4V 3.8Ah LiFePO4 Tubed - 2S1P
Type T - 2/LP38/PT/TE

159mm(l) x Ø 35mm

LiFePO4	3.2V 3.8Ah	3.2V 4.8Ah	6.4V 3.8Ah	6.4V 4.8Ah	12.8V 3.8Ah
NLP/1	X				
NLP/1S		X			
NLP/2			X		
NLP/2S				X	
TLP/1	X				
TLP/1S		X			
TLP/S2			X		
TLP/2S				X	
D2N/1	X				
D2N/1S		X			
D2N/2			X		
D2N/2S				X	
T2N/1	X				
T2N/1S		X			
T2N/2			X		
T2N/2S				X	
ACD/1	X				
ADM/1	X				
BMM/1	X				
S/ALP1	X				
MML/4W/TP60			X		
MML/8W/TP60					X

3 Cell - 3.2V 4.8Ah LiFePO4 Stick - 1S3P
Type 1 - 3/LP48/S/TE

230mm(l) x 24mm(w) x 22mm(h)
 Fixing Centres 220mm x M4

3 Cell - 3.2V 4.8Ah LiFePO4 Plate - 1S3P
Type 2 - 3/LP48/P/TE

69mm(l) x 55mm(w) x 21mm(h)
 Fixing Centres 20mm x 19mm x M3

3 Cell - 3.2V 4.8Ah LiFePO4 Tubed - 1S3P
Type T - 3/LP48/PT/TE

221mm(l) x 32mm(h) x 28mm(d)

3 + 3 Cell - 6.4V 4.8Ah LiFePO4 Sticks 2S3P
Type 6 - 6/LP48/TS/TE

2 x 230mm(l) x 24mm(w) x 22mm(h)
 Fixing Centres 220mm x M4 each

4 Cell - 12.8V 3.8Ah LiFePO4 Tubed 4S1P
Type T - 4/LP38/PT/TE

159mm(l) x 59mm(h) x 41mm(d)

3.2V 3.8Ah packs for use with ADM, ACD, BMM, D2N, S/ALP & NLP - /1 Ranges.
6.4V 3.8Ah packs for use with NLP, TLP, D2N, T2N - /2 Ranges.
3.2V 4.8Ah packs for use with NLP, TLP, D2N, T2N - /1S Ranges.
6.4V 4.8Ah packs for use with NLP, TLP, D2N, T2N - /2S Ranges.

LiFePO4	3.2V 3.8Ah	3.2V 4.8Ah	6.4V 3.8Ah	6.4V 4.8Ah	12.8V 3.8Ah
NLP/1	X				
NLP/1S		X			
NLP/2			X		
NLP/2S				X	
TLP/1	X				
TLP/1S		X			
TLP/S2			X		
TLP/2S				X	
D2N/1	X				
D2N/1S		X			
D2N/2			X		
D2N/2S				X	
T2N/1	X				
T2N/1S		X			
T2N/2			X		
T2N/2S				X	
ACD/1	X				
ADM/1	X				
BMM/1	X				
S/ALP1	X				
MML/4W/TP60			X		
MML/8W/TP60					X