



- Surface Mount
- White Polycarbonate body
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP65
- DDP (Deep Discharge Protection)
- Samsung LED's
- Kit of Legends for Ease of Stocking
- 25m Viewing Distance
- Basic, DALI-2 Or Wireless Self-test Operation
- Features Battery Temperature Protection

A stylish and compact IP65 rated exit sign suitable for wall mounting. The unit is available with either non-maintained, maintained, DALI-2 self-test, or wireless self-test operation. The fitting is not only more compact than the majority of LED exit signs, but offers an ingress protection of IP65 and a kit of legends for ease of installation and stocking.

The charger will cut-off if the Tc of the battery falls below 0 degrees C or above 55 degrees C. The product will however operate when required in emergency, should there be enough capacity remaining in the battery.

Order Codes

CE5S/M	Maintained IP65 Wall mounted Exit Sign
CE5S/NM	Non-Maintained IP65 Wall Mounted Exit Sign
CE5S/DA	Maintained DALI-2 Self-Test IP65 Wall Mounted Exit Sign
CE5S/LMEM	Maintained Wireless Self-Test IP65 Wall Mounted Exit Sign

Technical Details:

	CE5S/M	CE5S/DA
Mains Supply	230-240V AC 50/60 Hz	
Power Rating (Charging) *	5.7W 31mA $\lambda = 0.75$	5W 28mA $\lambda = 0.74$
Power Rating (Charged) *	0.2W 8mA $\lambda = 0.1$	0.3W 8mA $\lambda = 0.15$
Duration	3-Hours	
Recharge Period	24-Hours	
Battery Size & Type	3.2V 3.8Ah LiFePO4 Cells	
Charge Current	225mA Nominal	
Ingress Protection Rating	IP65	
Light Source	8 pcs Samsung LED	
Possible Arrow Configurations	Arrow Up, Arrow Down, Arrow Left & Arrow Right	

* Following its initial charge, the unit will spend 90% of its operational life in standby mode