



- Basic, DALI-2 or LiteMesh Wireless Operation
- Surface Mount (Wall or Ceiling)
- White Polycarbonate Body
- Extra Long Life LiFePO4 cells
- Ingress Protection Rating - IP20
- 25m viewing distance
- ISO7010 legends as standard
- DDP (Deep Discharge Protection)
- Samsung LED's
- TM65.2 Rating of 14.98kg CO<sup>2</sup>e
- Features Battery Temperature Protection

A stylish and compact Double Sided LED Exit Sign suitable for either wall or ceiling mounting. The unit is available in either a Switchable Maintained/Non-Maintained, DALI-2 Self-Test, or a LiteMesh Ready wireless version. The fitting is supplied with a PMMA screen printed legend plate which offers an impressive 25m viewing distance.

The legend panels are available in either Arrow Up (AU), Arrow Down (AD) or Arrow Left/Right (ALAR). Please note that all legends are single sided, apart from the ALAR which are double sided.

The charger will cut-off if the Tc of the battery falls below 0 degrees C or above 55 degrees C. The product will however operate when required in emergency, should there be enough capacity remaining in the battery.

## Order Codes

CE1S/M/**	Switchable Maintained
CE1S/DA/**	DALI-2 Type B, Switched Maintained Non-Dimmable, or Self-Test M3/NM3
CE1S/M/LMEM/**	LiteMesh Ready Wireless Maintained/Non-Maintained Self-Test

\*\* Please specify legend required AU, AD, or ALAR

## Technical Details:

	CE1S/M	CE1S/DA
Mains Supply	230-240V AC 50/60 Hz	
Power Rating Charging - Maintained *	5.7W 31mA $\lambda = 0.75$	5W 28mA $\lambda = 0.74$
Power Rating Charged *	0.2W 8mA $\lambda = 0.11$	0.26W 8mA $\lambda = 0.14$
Duration	3-Hours	
Recharge Period	24-Hours	
Battery Size & Type	3.2V 3.8Ah LiFePO4 Cells	
Charge Current	225mA nominal	
Ingress Protection Rating	IP40	
Weight	0.82Kg	

\* Following its initial charge, the unit will spend 90% of its operational life in standby mode